

- 57 -

CLAIMS

1. An ink jet printing apparatus for printing by
ejecting an ink containing a colorant from a print head,
5 comprising:

at least one ink absorber containing a coagulation
inhibitor and absorbing the ink discharged from the
print head, the coagulation inhibitor inhibiting a
coagulation of the colorant contained in the ink.

10

2. An ink jet printing apparatus according to claim
1, further comprising a platen supporting a print medium
from below in an area including a print area where the
print head ejects the ink onto the print medium;

15 wherein the at least one ink absorber is installed in
the platen to absorb the ink ejected outside the print
medium when a printing operation is performed on edge
portions of the print medium.

20 3. An ink jet printing apparatus according to claim
1, further comprising:

a preliminary ejection means for preliminary-ejecting
the ink from the print head; and

a preliminary ejection receiver for accommodating
25 the ink preliminary-ejected by the preliminary ejection
means;

wherein the at least one ink absorber absorbs the ink

- 58 -

accommodated in the preliminary ejection receiver.

4. An ink jet printing apparatus according to claim 1, further comprising:

5 an ink discharging means for discharging the ink from the print head by other than an ejection; and

an ink discharging path for transporting the ink discharged by the ink discharging means;

wherein the at least one ink absorber absorbs the ink
10 transported through the ink discharging path.

5. An ink jet printing apparatus according to claim 4, further comprising:

a reaction liquid head for ejecting a reaction liquid,
15 the reaction liquid accelerating a coagulation of colorant contained in the ink;

a reaction liquid discharging means for discharging the reaction liquid from the reaction liquid head; and

a reaction liquid discharging path for transporting
20 the reaction liquid discharged by the reaction liquid discharging means;

wherein the at least one ink absorber absorbs the ink transported through the ink discharging path and the reaction liquid transported through the reaction liquid
25 discharging path.

6. An ink jet printing apparatus according to claim

- 59 -

1, further comprising:

a reaction liquid head for ejecting a reaction liquid,
the reaction liquid accelerating a coagulation of
colorant contained in the ink.

5

7. An ink jet printing apparatus according to claim
1, further comprising:

a supply means for supplying the coagulation
inhibitor to the at least one ink absorber.

10

8. An ink jet printing apparatus according to claim
7, wherein said supply means comprises a coagulation
inhibiting liquid head for ejecting the coagulation
inhibitor.

15

9. An ink jet printing apparatus for printing by
ejecting an ink containing a colorant from a print head,
comprising:

an ink absorber for absorbing the ink discharged from
20 the print head; and

an application means for applying a coagulation
inhibitor to the ink absorber, the coagulation inhibitor
inhibiting a coagulation of the colorant contained in
the ink.

25

10. A method of manufacturing an ink absorber
applicable to the ink jet printing apparatus of claim 1,

- 60 -

comprising the steps of:

immersing the ink absorber in a liquid containing the
coagulation inhibitor; and

drying the ink absorber immersed with the liquid .

5

11. An ink absorber manufactured by the method of
claim 10.